



Offered by
LASER LAB SOURCE

manufactured by **KVANT
Scientific
Lasers**

405nm, Fiber-Coupled Source with Integrated Nichia Laser Diode

INTEGRATED NICHIA LASER DIODE

laser diode mounted to Peltier temperature controlled mount; output beam coupled into fiber



FAIL-SAFE LASER DIODE PROTECTION

pre-set current & temp limits + power surge clamp protect laser from damage

LDX-405NM-1200MW-KVAFC Laser Diode Source

- o Integrated Nichia NDV7375E Laser Diode
- o 1200mW Free-Space Output Power
- o ~1750mW Ex-Fiber Output Power
- o Temperature-Regulated Laser Head
- o Turn-Key Operation
- o Preconfigured Controller Included
- o Optional Benchtop Controller with Output Current and Temperature Control Capability



LDX-405NM-1200MW-KVAFC – FIBER-COUPLED LASER DIODE SOURCE MODULE

These scientific series lasers deliver up to 1200 mW of output power (free-space configuration) at a center wave-length of 405 nm. The source is a Nichia NDV7375E laser diode integrated to provide long-term high stability performance. These units are shipped fully calibrated & pre-tested with the matching current source and temperature controller as well as the required interface cables.

VERSATILE OPTICAL FIBER COUPLING SYSTEM

The KVAFC feature couples the optical fiber to the collimated free-space output port. Due to the physics of optical fiber coupling, the ex-fiber output power is approximately 15% – 20% lower than the collimated free-space output. The collimator can be removed from the laser head, which reduces the fiber-coupling loss to about 10%. This versatility allows increased efficiency for fiber-only applications, and provides flexibility for applications where both free-space and fiber-coupling are required.

CAREFUL DESIGN AND FEATURES PROTECT NICHIA LASER DIODE SOURCE

The control system is designed with multiple layers of protection for the internal Nichia laser source: an integrated LASORB diode on the current supply board offers a fail-safe clamp of the current / voltage to the integrated laser diode; and pre-set current and temperature limits. The LASORB eliminates the possibility of power surges and ESD damaging the laser.

The preset drive current range prevents the possibility of over-driving the laser diode, and the controller has an over-temperature shut down feature based on feedback from a sensor located against the laser package.

INCLUDED LASER DIODE CONTROL UNIT

The scientific laser source module includes a precision laser diode current and temperature controller unit. This controller is programmed with preset current and temperature limits to protect the laser diode. A front-panel adjustment knob on the front panel provides control of the laser output power level.

LIST PRICE INCLUDES LASER DIODE CURRENT / TEMPERATURE CONTROLLER UNIT

User adjustable current & laser output power controller with amplitude adjustment knob on front panel



Pre-set current limit & temperature limits keep laser diode in safe operating range; ESD & surge clamps protect laser diode from all power surges



OPTICAL SPECIFICATIONS

- Center Wavelength: 405nm (± 5 nm)
- User Adjustable Optical Output Power: 0 mW to 1200 mW *
- Spatial Mode: Multimode
- Beam Diameter (@ $1/e^2$): 4 mm
- Beam Divergence (half angle, mrad): 0.8
- Polarization: Linear
- Maximum Modulation Frequency: 10 kHz (100 kHz on request)
- Optical Power Stability (@ ambient $\pm 2^\circ\text{C}$): $<0.5\%$ (8hrs)

FIBER-COUPLED OUTPUT

- Fiber Core Diameter Options: 50 μm ; Others Available
- Contact Us To Discuss Fiber Termination Options
- Fiber Connector: FC/UPC (others on request)
- Collimating Lens Adapter: Included
- Default Beam Diameter Setting Ex-Collimator: 4mm (other on request)

PACKAGING & POWER SUPPLY

- Laser Module Dimensions (L x W x H): 92 mm x 61 mm x 46 mm
- Power Supply Included: 24 Volts, 2 Amps
- Current and Temperature Control Unit: Included
- Computer Interface: None



OPTIONAL BENCHTOP CURRENT / TEMPERATURE CONTROLLER

Temperature controller to fine-tune wavelength

Current controller to adjust laser diode power



BENCHTOP CONTROLLER LDC-405


The optional LDC-405 Benchtop Controller provides control of the laser drive current in order to adjust the laser output power. The temperature of the integrated laser diode can also be adjusted in order to fine-tune the laser output wavelength.

The benchtop controller hosts a modulation input, allowing the laser output to be modulated up to 10 kHz.

OUTPUT SPECTRUM OF NICHIA NDV7375E

The Nichia NDV7375E laser diode delivers the high reliability and stability resulting from Nichia's decades-long expertise in high performance semiconductor optical devices.

Typical Spectrum



PRODUCT SALES AND SERVICE:

Orders for this product are fulfilled by Laser Lab Source in North America and select international regions. It is manufactured by KVANT.

PRODUCT WARRANTY:

This product is sold with a full one-year warranty. It is warranted to be free from defects in material and/or workmanship for a period of one year from the date of shipment.



Laser Lab Source, a division of Research Lab Source Inc.
670 S. Ferguson St., Suite 3
Bozeman, MT 59718 USA

Phone: 406-219-1472

www.LaserLabSource.com

