



375nm, Fiber-Coupled Source with Integrated Nichia Laser Diode

INTEGRATED NICHIA LASER DIODE

laser diode mounted to Peltier temperature controlled mount; output beam coupled into fiber



NDU4116



FAIL-SAFE LASER DIODE PROTECTION

pre-set current & temp limits + power surge clamp protect laser from damage

LDX-375NM-70MW-KVAFC Laser Diode Source

- o Integrated Nichia NDU4116 Laser Diode
- o 70mW Free-Space Output Power
- o ~62mW Ex-Fiber Output Power
- o Choice of Low-OH Optical Fiber Core Size
- o Temperature-Regulated Laser Head
- o Turn-Key Operation
- o Preconfigured Controller Included
- o Optional Benchtop Controller with Output and Temperature Control Capability



LDX-375NM-70MW-KVAFC – FIBER-COUPLED LASER DIODE SOURCE MODULE

These scientific series lasers deliver up to 70 mW of output power (free-space configuration) at a center wave-length of 375 nm. The source is a Nichia NDU4116 laser diode integrated to provide long-term high stability performance. These units are shipped fully calibrated & pre-tested with the matching current source and temperature controller as well as the required interface cables.

VERSATILE OPTICAL FIBER COUPLING SYSTEM

The KVAFC feature couples the optical fiber to the collimated free-space output port. Due to the physics of optical fiber coupling, the ex-fiber output power is approximately 15% – 20% lower than the collimated free-space output. The collimator can be removed from the laser head, which reduces the fiber-coupling loss to about 10%. This versatility allows increased efficiency for fiber-only applications, and provides flexibility for applications where both free-space and fiber-coupling are required.

CAREFUL DESIGN AND FEATURES PROTECT NICHIA LASER DIODE SOURCE

The control system is designed with multiple layers of protection for the internal Nichia laser source: an integrated LASORB diode on the current supply board offers a fail-safe clamp of the current / voltage to the integrated laser diode; and pre-set current and temperature limits. The LASORB eliminates the possibility of power surges and ESD damaging the laser.

The preset drive current range prevents the possibility of over-driving the laser diode, and the controller has an over-temperature shut down feature based on feedback from a sensor located against the laser package.

INCLUDED LASER DIODE CONTROL UNIT

The scientific laser source module includes a precision laser diode current and temperature controller unit. This controller is programmed with preset current and temperature limits to protect the laser diode. A front-panel adjustment knob on the front panel provides control of the laser output power level.

LIST PRICE INCLUDES LASER DIODE CURRENT / TEMPERATURE CONTROLLER UNIT

User adjustable current & laser output power controller with amplitude adjustment knob on front panel



Pre-set current limit & temperature limits keep laser diode in safe operating range; ESD & surge clamps protect laser diode from all power surges



OPTICAL SPECIFICATIONS

- Center Wavelength: 375 nm (± 5 nm)
- Free-Space Optical Output Power: 0 to 70 mW* (*refer to note below*)
- Ex-Fiber Output Power: 55 mW - 62 mW* (*refer to note below*)
- Power Stability (@ ambient $\pm 2^{\circ}\text{C}$): $<0.5\%$ (8 hrs)
- Maximum Modulation Frequency (analog): 10 kHz
- RMS Noise (100 Hz to 10 MHz): $<0.3\%$
- Ambient Operating Temperature Range Minimum: 10°C
- Ambient Operating Temperature Range Maximum: 40°C
- Center Wavelength Tolerance: ± 5 nm

FIBER-COUPLED OUTPUT

- Contact Us To Discuss Fiber Termination Options
- Fiber Core Diameter Options: 50, 105, or 200 μm
- Fiber Connector: FC/UPC (others on request)
- Collimating Lens Adapter: Included
- Default Beam Diameter Setting Ex-Collimator: 4mm (other on request)

PACKAGING & POWER SUPPLY

- Packaging Dimensions (L x W x H): 87 mm x 60 mm x 45 mm
- Includes Pre-Configured OEM Current and Temperature Control Unit and AC/DC Converter Power Supply
- Optional Bench-top Controller with Full Front Panel Display Available (request pricing)
- Computer Interface: None



OPTIONAL BENCHTOP CURRENT / TEMPERATURE CONTROLLER

Temperature controller to fine-tune wavelength

Current controller to adjust laser diode power



Key switch power supply ON/OFF

Laser diode ON/OFF

BENCHTOP CONTROLLER LDC-405

The optional LDC-405 Benchtop Controller provides control of the laser drive current in order to adjust the laser output power. The temperature of the integrated laser diode can also be adjusted in order to fine-tune the laser output wavelength.


The benchtop controller hosts a modulation input, allowing the laser output to be modulated up to 10 kHz.

STANDARD CONTROLLER FUNCTIONALITY

The scientific laser module includes a current and temperature control unit, pre-programmed with current and temperature limits to protect the Nichia laser diode in the laser head. This standard controller is well suited to many applications.

INTEGRATED NICHIA LASER DIODE

laser diode mounted to TEC temperature controlled mount; collimated beam output



INCLUDES CURRENT & TEMPERATURE CONTROL UNIT

controller unit has pre-set limits to keep laser diode in safe operating range; user adjustable output power knob

PRODUCT SALES AND SERVICE:

Orders for this product are fulfilled by Laser Lab Source in North America and select international regions. It is manufactured by KVANT.

PRODUCT WARRANTY:

This product is sold with a full one-year warranty. It is warranted to be free from defects in material and/or workmanship for a period of one year from the date of shipment.



Laser Lab Source, a division of Research Lab Source Inc.
670 S. Ferguson St., Suite 3
Bozeman, MT 59718 USA

Phone: 406-219-1472

www.LaserLabSource.com

