



*This product is sold  
and supported  
in the USA by*



**LASER LAB SOURCE**  
marketplace for **Scientists & Engineers**

**Laser Diode Part Number: 1064LD-1-0-0**

---

---

**contact@laserlabsource.com | 800-887-5065**

## 1064 nm laser diode

700 mW / singlemode fiber / Butterfly package

Reference: 1064LD-1-0-0

Technology : Single mode Fabry Perot\*

SPECIFICATIONS	Unit	Min	Typ	Maximum
Output Power (kink free)	mW	700		
Center Wavelength (Chip regulated at >~30°C)	nm	1063	1064	1065
Spectral Width	nm(FWHM)		2.5	
Threshold Current	mA			70
Operating Current	mA		1200	1500
Operation Voltage	V		1.7	2.0
Wavelength shift w Temperature	nm/°C		0.35	
Polarization Extinction Ratio	dB	13		
Internal Photodiode Responsivity	mA/W	0.5		10
Internal Photodiode Dark Current	nA			100
TEC current (Case @ 75°C)	A			1.4
TEC Voltage (Case at 75°C)	V			3.2
Internal thermistor (25°C)	kOhm	9.5		10.5
Fiber type	PM fiber : SM98-PS-U25D-H or Nufern PM980			
Fiber bend radius	mm	16 (abs min)		
Coating diameter	µm	230	250	270
Storage case temperature	°C	-40 (abs min)		85 (abs max)
Operating case temperature	°C	-20 (abs min)		75 (abs max)
Lead soldering temperature	°C			280
Laser diode reverse voltage	V			2.0
Pigtail Termination	Ferrule			
Polarization state	Aligned to the slow axis			

\*: See our tutorial : [fiber coupled laser diode](#)

Form factor:

Laser diode pinning :

