

LT-6500 (T15)

CW ARRAY

Lasertel CW arrays are based on a patented, extremely flexible assembly technology that eliminates common failure mechanisms associated with conventional CW array.

WAVELENGTHS:

- ✦ 808
- ✦ 830
- ✦ 885
- ✦ 976



LT-6500 (T15) CW ARRAY

WAVELENGTH: 808

TYPICAL OPTICAL PARAMETERS (@25°C)		UNITS	VALUE		
Output Power per Bar		W	40	60	80
Operation Mode			CW	CW	CW
Emission Length per Bar		mm	10	10	10
Number of Bars		#	60 to 85	60 to 85	60 to 85
Bar Pitch		mm	1.2 or 1.8	1.2 or 1.8	1.2 or 1.8
Maximum Array Output Power		W	3400	5100	6800
Beam Divergence					
Fast Axis (FWHM)		°	38	38	38
Slow Axis (FWHM)		°	12	12	12
TYPICAL ELECTRICAL PARAMETERS (@25°C)					
Power Conversion Efficiency		%	55	52	50
Threshold Current		A	8	12	16
Operating Current		A	45	65	85
Operating Voltage per Bar		V	1.9	1.9	1.9
THERMAL PARAMETERS					
Operating Temperature		°C	10 to 50	10 to 50	10 to 50
Storage Temperature		°C	0 to 70	0 to 70	0 to 70

LT-6500 (T15) CW ARRAY

WAVELENGTH: 830

TYPICAL OPTICAL PARAMETERS (@25°C)		UNITS	VALUE		
Output Power per Bar		W	40	60	80
Operation Mode			CW	CW	CW
Emission Length per Bar		mm	10	10	10
Number of Bars		#	60 to 85	60 to 85	60 to 85
Bar Pitch		mm	1.2 or 1.8	1.2 or 1.8	1.2 or 1.8
Maximum Array Output Power		W	3400	5100	6800
Beam Divergence					
Fast Axis (FWHM)		°	38	38	38
Slow Axis (FWHM)		°	12	12	12
TYPICAL ELECTRICAL PARAMETERS (@25°C)					
Power Conversion Efficiency		%	55	52	50
Threshold Current		A	8	12	16
Operating Current		A	45	65	85
Operating Voltage per Bar		V	1.9	1.9	1.9
THERMAL PARAMETERS					
Operating Temperature		°C	10 to 50	10 to 50	10 to 50
Storage Temperature		°C	0 to 70	0 to 70	0 to 70

LT-6500 (T15) CW ARRAY

WAVELENGTH: 885

TYPICAL OPTICAL PARAMETERS (@25°C)		UNITS	VALUE		
Output Power per Bar		W	40	60	80
Operation Mode			CW	CW	CW
Emission Length per Bar		mm	10	10	10
Number of Bars		#	60 to 85	60 to 85	60 to 85
Bar Pitch		mm	1.2 or 1.8	1.2 or 1.8	1.2 or 1.8
Maximum Array Output Power		W	3400	5100	6800
Beam Divergence					
Fast Axis (FWHM)		°	38	38	38
Slow Axis (FWHM)		°	12	12	12
TYPICAL ELECTRICAL PARAMETERS (@25°C)					
Power Conversion Efficiency		%	55	52	50
Threshold Current		A	8	12	16
Operating Current		A	45	65	85
Operating Voltage per Bar		V	1.9	1.9	1.9
THERMAL PARAMETERS					
Operating Temperature		°C	10 to 50	10 to 50	10 to 50
Storage Temperature		°C	0 to 70	0 to 70	0 to 70

LT-6500 (T15) CW ARRAY

WAVELENGTH: 976

TYPICAL OPTICAL PARAMETERS (@25°C)		UNITS	VALUE		
Output Power per Bar		W	40	60	80
Operation Mode			CW	CW	CW
Emission Length per Bar		mm	10	10	10
Number of Bars		#	60 to 85	60 to 85	60 to 85
Bar Pitch		mm	1.2 or 1.8	1.2 or 1.8	1.2 or 1.8
Maximum Array Output Power		W	3400	5100	6800
Beam Divergence					
Fast Axis (FWHM)		°	38	38	38
Slow Axis (FWHM)		°	12	12	12
TYPICAL ELECTRICAL PARAMETERS (@25°C)					
Power Conversion Efficiency		%	55	52	50
Threshold Current		A	8	12	16
Operating Current		A	45	65	85
Operating Voltage per Bar		V	1.9	1.9	1.9
THERMAL PARAMETERS					
Operating Temperature		°C	10 to 50	10 to 50	10 to 50
Storage Temperature		°C	0 to 70	0 to 70	0 to 70

LT-6500 (T15) CW ARRAY

TECHNICAL DRAWING

DIMENSIONS IN MM

