

MDL-E-1060/1~40mW



**NARROW LINEWIDTH
DIODE LASER AT 1060nm**



Narrow linewidth diode laser module at 1060nm is made features of narrow spectral linewidth, stable wavelength, long lifetime and easy operating, which is widely used in precision measurement, high resolution spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	1060±10
Operating mode	CW
Output power (mW)	>1, 2, 3, ...,40
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Transverse mode	Near TEM ₀₀
Spectral linewidth (nm)	<0.06, <0.03(extra heatsink)
M ² factor	<1.5
Beam diameter at the aperture (1/e ² ,mm)	~3.5
Beam divergence, full angle (mrad)	<1.0
Warm-up time (minutes)	<15
Beam height from base plate (mm)	30
Operating temperature (°C)	20~30
Power supply (85-264VAC)	PSU-III-FDA
Expected lifetime (hours)	10000
Warranty	1 year



MDL-E-1060	PSU-III-FDA
 <p>122.5(L) ×65(W) ×50 (H) mm³, 1.0kg</p>	 <p>171(L) ×130(W) ×62.2 (H) mm³, 1.2kg</p>