

# NLK1E5EAAA

1360-1460 nm DFB laser diode in a butterfly-type 14 pin package with thermo-electric cooler. Pigtail fiber is connectorized with an FC/PC connector.

## FEATURES

- \* Wavelength Range 1360 - 1460 nm, ITU-T grid wavelength
- \* Fiber Output Power 10mW

## ABSOLUTE MAXIMUM RATINGS( $T_{sub}=25deg.C$ )

Parameter	Symbol	Ratings	Units
Laser diode reverse voltage	$V_R$	2.0	V
Laser diode forward current	$I_F$	150	mA
Operating case temperature	$T_{case}$	-5 to 70	deg.
Storage temperature	$T_{stg}$	-40 to 85	deg.
Photodiode reverse voltage	$V_{DR}$	10	V
Photodiode forward current	$I_{DF}$	10	mA
Peltier current	$I_P$	1.4	A

## ELECTRICAL/OPTICAL CHARACTERISTICS( $T_{sub}=25deg.C$ )

Parameter	Symbol	Condition	Min.	Typ.	Max.	Units
Forward voltage	$V_F$	$I_F=30mA$		1.2	1.6	V
Threshold current	$I_{(TH)}$	CW		10	20	mA
Fiber output power	$\phi_c$	CW, $I_F=80mA$	10			mW
Peak wavelength	$\lambda_p$	CW, $\phi_c=10mW$	-1	ITU-T	+1	nm
Spectral linewidth*	$\Delta\lambda$	CW, $\phi_c=10mW$		2		MHz
Side mode suppression ratio	SMS	CW, $\phi_c=10mW$	35			dB
Monitoring Current(PD)	$I_{R(E)}$	CW, $\phi_c=10mW$	0.1			mA
Dark current(PD)	$I_{(0)}$	CW, $V_{DR}=5V$			100	nA
Tracking error	$E_R$	$I_{R(E)}=constant$	-0.5		+0.5	dB
Cooling capacity*	$\Delta T_{PE}$	$\phi_c=10mW, T_{case}=70deg$	45			deg.
Peltier current	$I_{PE}$	$T_{case}=-5 to 70deg.$			1	A
Peltier voltage	$V_{PE}$	$T_{case}=-5 to 70deg.$			2	V
Thermister resistance*	R	$T_{sub}=25deg.$		10		k $\Omega$
Isolation*	$I_s$	$T_{sub}=25deg.$		30		dB