



*This product is sold
and supported
in the USA by*



LASER LAB SOURCE
marketplace for **Scientists & Engineers**

contact@LaserLabSource.com

800.887.5065

CoBriteDX - Laser

Features

- ✓ Hosts 1 to 4 laser ports
 - ✓ Polarization Maintaining Output
- ✓ Multiple Laser variants available
- ✓ Line width down to < 25kHz
- ✓ Remote control
 - ✓ USB & Ethernet connectivity
 - ✓ SCPI Style commands
- ✓ Integrated Web Server for browser-based control
 - ✓ Access device from any smartphone or PC via Browser
- ✓ Large Touch Display Panel for intuitive local control
- ✓ 19" Rack mountable
 - ✓ 2HE – 19" Half width

Applications

- ✓ DWDM transport testing
- ✓ coherent Transmission
 - ✓ Local Oscillator
 - ✓ Transmitter Laser
- ✓ versatile Light source



CoBrite is a versatile tunable Laser light instrument that allows standalone operation by an intuitive local touch display. The chassis can be equipped with 1 to 4 tunable lasers to meet your specific needs.


Remote operation via an integrated web server allows control using any browser-based device such as smartphones eliminating the need for complex software installations.

An integrated AC power supply makes this solution ultra portable while it is compatible with the 19" rackmount standard.

Automated remote control is achieved via USB or Ethernet by SCPI command control. It empowers users to setup and perform complex automated tasks within minutes.

Optical connectors are tool-free user removable allowing instant access for fiber cleaning.

Optical Parameter	Laser Type N	Laser Type S	Laser Type E	Unit
Frequency range; C – Band L – Band	190.70 – 196.65 (1524.5 - 1572nm) 186.00 – 191.1 (1568.8 – 1611.7nm)	191.12 – 196.25 (1527.6 – 1568.6nm) Not available	191.4 – 196.1 (1528.8 – 1566.3nm) Not available	THz
Channel Spacing	Continuous	Continuous	Continuous	GHz
Frequency fine tune resolution	1	10	10	MHz
Frequency fine tune range	+/- 6	+/- 10	+/- 10	GHz
Optical Power tuning range for any frequency C Band L Band	10.0 – 16.0 9.0 – 14.5	8.8 – 17.8 –	10 – 16.5 –	dBm
Spectral Line width; 3dB instantaneous, 3.5us (Lorentzian contribution)	< 100 25 typical	< 100 80 typical	Max: 400	kHz
Frequency accuracy over Lifetime Over 24 hours	+/- 2.5 0.3	+/- 1.5 0.3	+/- 1.5 0.3	GHz
SMSR; Side mode suppression ratio; measured with 0.1nm RBW	> 40 55 typical	> 40	> 40	dB
RIN (10MHz to 3GHz)	-145 (10 MHz to 44GHz, 7dBm)	-140 (100kHz – 20MHz) -150 (20MHz – 1GHz)	-140 (100kHz – 20MHz)	dB/Hz
Power accuracy over tuning range	+/- 0.5	+/- 0.5	+/- 0.5	dB
Tuning speed (max/typical)	15 / 10	2 / 1.0	7 / 5	s
Output Connector	FC/APC, FC/PC or SC/PC			
Output power accuracy over Lifetime Over 1 hour Over 24 hours				-/+1 +/- 0.01 (typ.) +/- 0.03 (typ.)
Output power setting resolution				0.1
Optical Fiber	Polarization- maintaining PANDA type Fiber, PER > 18dB, 25typ.			



Device Parameter

Operating Temperature	0 to 40°C	non-condensing
Storage Temperature	-20°C to 60°C	non-condensing
Size of device (H x W x D)	89 x 206 x 235mm 3.51" x 8.12" x 9.06"	
Power Supply	100-240 VAC, 0.5A, 50/60Hz	

Ordering Information

CBDX	-XY-XY-XY-XY	-XX
Article	Laser Configuration, per Port:	Connector
CoBriteDX	X: Laser Type (N,S,E) Y: Laser Band - (C, L) band XY = NN: No laser equipped	FA = FC/APC FP = FC/PC SP = SC/PC
CBDX-ACC-RM-x	19" Adaptor plate for rack mount, 2 HE 1: 1 Laserchassis; 2: 2 Laser chassis	

* APC type connector only

Contact information

ID Photonics GmbH
Anton-Bruckner-Str. 6
85579 Neubiberg
GERMANY
Tel.: + 49 (0) 89 – 201 899 16

info@id-photonics.com
www.id-photonics.com



Invisible Laser Radiation
Class 1M Laser Product
EN 60825-1: IEC 60825-1