



Item Number: 6417-0001**Item Description: 1710nm, 60W, 400µm fiber-coupled module with options**

Parameter	Units	Minimum	Typical	Maximum
Optical				
CW Output Power from Fiber	W	60		
Center Wavelength	nm	1690	1710	1730
Spectral Width (FWHM)	nm			20
Fiber Core Diameter	µm		400	
Fiber NA	-		0.22	
Temperature tuning coefficient	nm/°C		0.7	
Electrical (FCA)				
Operating Current (I _{OP})	A		45	55
Operating Voltage (V _{OP})	V		7.9	9
E-O conversion efficiency	%	15	17	
Thermal				
Operating Temperature	°C	20	25	30
Storage Temperature	°C	-20		70
Mechanical				
Module dimensions	mm		200 x 190 x 62	
Fiber length	m		User defined	
Fiber Input connector	-		HP-SMA 905	
Thermistor				
Type	-		NTC	
Resistance at 25°C	KΩ		10	
Optional Aiming Beam				
Wavelength	nm			635 +/- 10
Optical power	mW			>=1.0
Optional Monitoring Photo Diode				
Output signal at full power	µA	50		250
Control signal				
Interfacing		DB-15 connector at module back wall		

Notes

1. Specified performance to be tested at 25C module base temperature
2. Non-condensing operating environment required



Pin number	Assignment
1	Thermistor
2	Thermistor
3	Not used
4	Not used
5	Monitor Photodiode +
6	Monitor Photodiode -
7	Not used
8	Not used
9	Not used
10	Not used
11	Not used
12	Not used
13	Not used
14	Aiming beam +5V DC
15	Aiming beam ground

