



Datasheet

**RLDG55**  
Red Laser Diode

Features


- Single Transverse Mode
- Can Type:  $\phi 5.6\text{mm}$

Absolute Maximum Ratings


Item	Symbol	Absolut max. Ratings	Unit
Forward Current	If	300	mA
Allowable Reverse Voltage	Ir (LD)	85	mV
Storage Temperature	Tstg	-40 ~ +100	°C
Operating Case Temperature	Tc	-5 ~ +60	°C

Optical Characteristics

Item	Condition	Symbol	Min	Typ	Max	Unit
Optical Output Power (25°C)	If=260mA	Po	-	200	-	mW
Dominant Wavelength (25°C)	If=260mA	$\lambda_d$	632	635	638	nm
Threshold Current (25°C)	CW	I <sub>th</sub>	55	80	105	mA
Slope Efficiency	CW	$\eta$	0.5	0.95	1.2	mW/A
Operating Voltage	If=260mA	V <sub>op</sub>	2.3	2.7	3.0	V
Beam Divergence	If=260mA	$\theta_{//}$	5	9	13	deg.
		$\theta_{\perp}$	13	18	23	deg.



Dimensions



New Laser Generation

Fon: +49 561 70562870

Fax: +49 561 70562871

Mail: info@lasertack.com

Web: www.lasertack.com