



# 1310nm, 5mW Fiber-Coupled DFB Laser Diode Isolator, Photodiode, PM Fiber, FC/APC Connector

## RLS / 1310NM-5MW-IPD-PMF

### OPTICAL SPECIFICATIONS

- Output Wavelength: 1310 nm  $\pm$ 10 nm
- Output Power: 5 mW
- Spectral Width (FWHM): 0.3 nm
- Wavelength Temp. Coefficient: 0.09 nm/ $^{\circ}$ C
- Beam Type: Gaussian Beam
- Laser Type: DFB (Distributed Feedback)
- Isolation: 30 dB (typ)
- Includes Integrated Photodiode

### FIBER SPECIFICATIONS

- Fiber Type: Polarization Maintaining Fiber
- Polarization Extinction Ratio: 15 dB
- Fiber Core: 9  $\mu$ m
- N.A.: 0.12
- Fiber Length: >80 cm
- Fiber Connector: FC/APC (Other Types Available; Inquire)
- Alignment: Slow Axis Aligned to FC Key

### ELECTRICAL SPECIFICATIONS

- Threshold Current: 5 mA (typ)
- Operating Current: 70 mA (typ)
- Operating Voltage: 1.4 V (typ)
- Max LD Reverse Voltage: 2.0 V
- PD Current: 0.1 mA
- PD Reverse Voltage Max: 15 V

### GENERAL SPECIFICATIONS

- Operating Temperature Range: -20 $^{\circ}$ C – 50 $^{\circ}$ C
- Recommended Operating Temp: 25 $^{\circ}$ C
- Storage Temperature Range: -40 $^{\circ}$ C – 100 $^{\circ}$ C
- Lead Soldering Temperature: 260 $^{\circ}$ C

