

# 793nm, 200 $\mu$ m, Conduction-Cooled, Fiber-Coupled, Two-Bar Module

## Features

- Single wavelength
- High coupling efficiency
- Thermal interface by base-plate
- Water manifold for water cooling

## Optional Accessories

- Integrated pointer laser and power meter
- Integrated temperature sensor
- Fiber interlock
- TE adapter for thermo electric cooling
- Exchangeable protection window



## Device Specification

Optical Parameters <sup>1</sup>	Units	
Center Wavelength Range <sup>3</sup>	nm	793
Center Wavelength Tolerance	nm	$\pm 3$
Output Power <sup>2</sup>	W	60
Spectral Width (FWHM)	nm	<4
Slope Efficiency	W/A	>1.6
Wavelength Temp. Coefficient	nm/ $^{\circ}$ C	$\sim 0.27$

Fiber Parameters		
Numerical Aperture	NA	0.22
Fiber Core Diameter	$\mu$ m	200
Fiber Connector		HP-SMA 905 with Free Standing Fiber Tips

Electrical Parameters <sup>1</sup>		
Power Conversion Efficiency	%	>40
Threshold Current ( $I_{TH}$ )	A	<9
Operating Current ( $I_{OP}$ )	A	<60
Operating Voltage ( $V_{OP}$ )	V	<4

Thermal Parameters		
Operating Temperature <sup>2, 3, 4</sup> (Cooling Plate)	$^{\circ}$ C	+20 to +25
Operating Temperature <sup>2, 3, 4</sup> (Diode Laser Module)	$^{\circ}$ C	+30 to +35
Storage Temperature <sup>3, 4</sup>	$^{\circ}$ C	0 to +55
Coolant Flow Rate	l/h	150 to 200
Operating Water Temperature	$^{\circ}$ C	+20 to +25
Maximum Particle Size	$\mu$ m	<10
Recommended Cooling Capacity	W	>160

<sup>1</sup>Data at 25 $^{\circ}$ C cold plate temperature, unless otherwise stated.


<sup>2</sup>Reduced lifetime if used above nominal operating conditions.

<sup>3</sup>Others available upon request.

<sup>4</sup>A non-condensing environment is required for storage and operation below the ambient dew point.

# 793nm, 200 $\mu$ m, Conduction-Cooled, Fiber-Coupled, Two-Bar Module

## Package Dimension



©2012 DILAS. All rights reserved. DILAS reserves the right to change products specifications without notice. For handling precautions, please reference the general handling instruction manual.

For complete details, please contact your local DILAS sales representative or visit our website at [www.DILAS.com](http://www.DILAS.com).

**Europe**  
**DILAS Diodenlaser GmbH**  
 Galileo-Galilei-Straße 10  
 55129 Mainz  
 Germany  
 Phone: +49 (0)6131 9226 0  
 Fax: +49 (0)6131 9226 257  
 Email: [sales@DILAS.de](mailto:sales@DILAS.de)

**North America**  
**DILAS Diode Laser, Inc.**  
 9070 South Rita Road  
 Suite 1500  
 Tucson, AZ 85747  
 Phone: +1 (520) 232-3480  
 Fax: +1 (520) 232-3499  
 Email: [sales@DILAS-INC.com](mailto:sales@DILAS-INC.com)

**China & Taiwan**  
**DILAS Diodenlaser GmbH**  
 China Sales Office  
 Room 206, Sunplus Technology, Bldg. 2  
 No. 1077 Zu Chongzhi Road  
 Hi-Tech Park, Shanghai 201203,  
 P.R. China  
 Phone: +86 (0) 21-6855-2216  
 Fax: +86 (0) 21-5027-3793  
 Email: [sales@dilas-china.com.cn](mailto:sales@dilas-china.com.cn)