

- High Power CW Operation- 0.8 Watt
- High Brightness- 100 μm Aperture
- Wavelength 760 ± 3 nm Standard

The LDX-3110-760 is a high brightness, high power, multimode laser diode. These broad-area, gain-guided lasers are produced using MOCVD growth. The 760 nm wavelength is well suited for photodynamic therapy, and other medical applications which require a large tissue penetration depth.

These devices are available on a open heatsink package, a variety of hermetically sealed TO-packages, or in a hermetically sealed High-Heat-Load package which has an integral thermoelectric cooler, thermistor, and monitor photodiode. Other package options are available; please inquire.

Device ratings:

Parameter	Min.	Typ.	Max.	Units
Output Power @ 15 °C	800		1000	mW
Threshold Current	300	400	600	mA
Operating Current at Rated Power	1200	1500	1800	mA
Operating Temperature	0	15	25	°C

Device characteristics at 15°C and at 800 mW output power:

Parameter	Min.	Typ.	Max.	Units
Forward Voltage	1.6	1.8	2.0	Volts
Wavelength	757	760	763	nm
Spectral Width		1.5	3	nm (FWHM)
Divergence- Parallel	5	7	9	degrees (FWHM)
Divergence- perpendicular	40	55	60	degrees (FWHM)
Polarization Ratio		>50:1		
Aperture Size		100 x 1		μm
Slope Efficiency	0.60	0.8	1.0	mW/mA