

## 808 nm 2 W Laser Diode

- High Power CW Operation- 2 watts
- High Brightness- 100  $\mu\text{m}$  emitter size
- Wavelength 808 nm standard
- Divergence 10° x 32° FWHM

The LDX-3210-808 laser diode is a high power, high brightness, multimode infrared laser diode. These broad-area, gain-guided lasers offer high efficiency, low threshold current, and excellent reliability.

These devices are available on an open heatsink (C-mount) package, in hermetically sealed TO-3 packages, as well as other package options; please inquire.

Device ratings:

Parameter	Min.	Typ.	Max.	Units
Output Power @ 20 °C		2000	2500	mW
Threshold Current	200	250	400	mA
Operating Current at Rated Power	1700	1900	2200	mA
Operating Temperature	0	20	40	•C

Device characteristics at 20°C and at 2000 mW output power:

Parameter	Min.	Typ.	Max.	Units
Forward Voltage	1.8	2.0	2.2	Volts
Wavelength	800	804	808	nm
Spectral Width		2	4	nm (FWHM)
Divergence- Parallel		10	12	degrees (FWHM)
Divergence- perpendicular	28	32	36	degrees (FWHM)
Polarization Ratio		>50:1		
Aperture Size		100 x 1		$\mu\text{m}$
Slope Efficiency	1.0	1.2	1.3	mW/mA