



# 520nm, 40mW Fiber-Coupled Laser Diode

## Integrated Photodiode, 3μm Single-Mode Fiber, FC/PC Connector

### RLS / 520NM-40MW-PD-SMF

#### OPTICAL SPECIFICATIONS

- Output Wavelength: 520 nm ±10 nm
- Output Power: 40 mW
- Spectral Width (FWHM): 2.0 nm
- Wavelength Temp. Coefficient: 0.05 nm/°C
- Beam Type: Gaussian Beam
- Laser Type: Fabry-Perot
- Includes Integrated Photodiode

#### FIBER SPECIFICATIONS

- Fiber Type: Single Mode Fiber
- Fiber Core: 3 μm
- N.A.: 0.12
- Fiber Length: >80 cm
- Fiber Connector: FC/PC (Other Types Available; Inquire)

#### ELECTRICAL SPECIFICATIONS

- Threshold Current: 45 mA (typ)
- Operating Current: 240 mA (typ)
- Operating Voltage: 7.5 V (typ)
- Max LD Reverse Voltage: 2.0 V
- PD Current: 0.1 mA
- PD Reverse Voltage Max: 30 V

#### GENERAL SPECIFICATIONS

- Operating Temperature Range: -20°C – 60°C
- Recommended Operating Temp: 25°C
- Storage Temperature Range: -40°C – 85°C
- Lead Soldering Temperature: 260°C, 10 sec.

