



635nm, 50mW Fiber-Coupled Laser Diode

Integrated Photodiode, 4μm Single-Mode Fiber, FC/PC Connector

RLS / 635NM-50MW-PD-4UM-SMF

OPTICAL SPECIFICATIONS

- Output Wavelength: 638 nm ±10 nm
- Output Power: 50 mW
- Spectral Width (FWHM): 2.0 nm
- Wavelength Temp. Coefficient: 0.2 nm/°C
- Beam Type: Gaussian Beam
- Laser Type: Fabry-Perot
- Includes Integrated Photodiode

FIBER SPECIFICATIONS

- Fiber Type: Single Mode Fiber
- Fiber Core: 4 μm
- N.A.: 0.12
- Fiber Length: >80 cm
- Fiber Connector: FC/PC (Other Types Available; Inquire)

ELECTRICAL SPECIFICATIONS

- Threshold Current: 60 mA (typ)
- Operating Current: 220 mA (typ)
- Operating Voltage: 2.7 V (typ)
- Max LD Reverse Voltage: 2.0 V
- PD Current: 0.3 mA
- PD Reverse Voltage Max: 30 V

GENERAL SPECIFICATIONS

- Operating Temperature Range: -10°C – 60°C
- Recommended Operating Temp: 25°C
- Storage Temperature Range: -40°C – 85°C
- Lead Soldering Temperature: 260°C, 10 sec.

